

HiStone

Self-Checkout System | Vision X | HS210R

Key Features

- ❑ 21.5" True flat capacitive touch screen enhancing user experience
- ❑ Multi-modular design allowing for self-service or self-checkout customization to suit a variety of hospitality or retail environments
- ❑ Flexible operational scenarios; wall mount or floor stand
- ❑ Lightweight ultra-slim design



| MODEL | | HS210R | | |
|----------------------|--|---|--|---|
| Processor | | ARM RK3288 (4core) 1.6GHz | | |
| | | ARM RK3288 (4core) 1.8GHz | | |
| Operating System | | Android 7.1 | | |
| Memory | | 2GB | | |
| Storage | | 16GB eMMC | | |
| Display Panel | | 21.5" LCD 16:9 Standard resolution: 1920 x 1080 | | |
| Touch Screen | | True flat capacitive touch screen | | |
| Power Supply | | 150W (Integrated) | | |
| Speaker | | 2* 5W Speaker | | |
| I/O Ports | | USB | 1* 2.0 | |
| | | LAN | 1* RJ45 100M/1000M Gigabit | |
| Default Peripherals | | Printer | Integrated 80mm thermal printer | |
| | | Scanner | Integrated: supports 1D/2D barcodes | |
| | | Wi-Fi® | Dual-band 802.11a/b/g/n/ac 2.4GHz/5GHz | |
| | | Bluetooth | BT4.0 | |
| Optional Peripherals | | I/O Ports | USB | 3* 2.0 |
| | | | Serial | 3* DB9 |
| | | Camera | | Face ID |
| | | | | Security Camera |
| | | MSR | | Not supported |
| | | RFID | | Not supported |
| | | FPR | | Not supported |
| | | Status Indicator | | Three-color status indicator light |
| | | Shelving | | Small shelving unit (for scale) |
| | | | | Large shelving unit |
| | | Stand | | Desktop stand |
| | | | | Floor stand |
| | | | | Small plate: metal or plastic (to be bolted to the floor) |
| | | | | Medium plate: metal or plastic (no need for screws) |
| | | | | Large plate: metal or plastic (no need for screws) |
| | | Wall Mount | | Wall mount bracket |
| | | Bracket | | EFTPOS holder |
| | | | | Bag holder (hooks) |
| | | | | Disinfectant or sanitizer bottle holder |
| | | | | External printer holder |
| Scale | | Range: 60kg Size: 450 x 600 mm | | |
| Bag Recycling | | Bag recycling module | | |

| MODEL | | HS210R |
|--------------------|-----------|---|
| Dimensions (WxDxH) | | 1690 x 1092 x 482 mm |
| Weight | | 40kg (Core Module & Stand) |
| Operating Voltage | | 90 ~ 132/180 ~ 264VAC |
| Environment | Operating | 10°C - 40°C / 30%-75% RH non-condensing |
| | Storage | -5°C - 50°C / 30%-80% RH non-condensing |
| EMC and Safety | | CE/FCC Pending |
| Colour | | Black or White |

Disclaimer: All products specifications are subject to change without notice.

- Optional Security Camera
- Optional Small Shelving Unit
- Optional Security Scale
- Optional Bag Recycling Module



- Optional Large Shelving Unit
- Back-to-back configuration with large metal plate for stability
- Bag Holder (hooks)