



- USB and Ethernet Connection Ports
- Modular Design Saves Counter Space
- Replace Paper Rolls Without Disconnecting Scanner
- Economical and Easy Thermal Printing
- Print Graphics on Your Receipts
- Engineered for Durability

Prints receipts right at your check scanner. Engineered to fit under Digital Check SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

SmartSource ReceiptNOW Elite

Engineered to fit beneath the SmartSource Elite series scanners and network-enable your printer. This printer includes both an Ethernet and USB connection, and can operate in either environment.

ReceiptNOW printers are network-ready, and come with two rear Ethernet ports, allowing you to connect the printer with the Expert Elite (Ethernet) scanner on the same line.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

Compatibility

- USB or Ethernet interface
- Full 108 standard and international fonts with barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

Customizable Teller Receipts

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper



PRODUCT SPECIFICATIONS

Model SRNELITE-ETH2-E – ReceiptNOW with USB and Ethernet	Interface USB or Ethernet Standard ESC/POS Command Set OPOS & JavaPOS, Auto Status Back (ASB)
Printer Dimensions ReceiptNow Elite Height: 5.7 in (14.48 cm) Width: 5.3 in (13.46 cm) Length: 10.5 in (26.67 cm)	Included Accessories USB 2.0 cable 1 ft. Ethernet cable International 100-240VAC, 50/60Hz power supply
Printing/Feed/Cut Direct Thermal Printer Black and Two Color Capability (with 2-color paper) Maximum print speed is 250mm/sec, two-color printing speed 100mm/sec, gray print speed 100mm/sec. Resolution: 203 x 180 dpi 95 Alphanumeric, 13 International Characters with Kanji True Type Fonts available when being driven as a Windows printer 1D/2D Bar Code Fonts 512K On-board Logo Flash Full/Partial Auto Cutter	Graphic Receipt Customization Multiple Graphics Can be Placed Anywhere Custom Messages Watermarks
Controls On/Off Switch Paper Empty/Low LED's with audible alerts Paper Feed Button Paper Width Adjustment Power Indicator	Supported Operating Systems Windows 8.1®, Windows 10®, Windows 11® (32/64 bit)
Paper/Loading Standard, Security, Non-BPA, 2-color Paper Paper Widths: 2.4 in to 3.25 in (6.1 cm to 8.3 cm) Paper Roll Diameter: 3.25 in (8.3 cm) Slide Out Tray, Drop-in Paper	Environmental Operating Temperature: 41° - 104° F (5° - 40° C) Operating Humidity: 20 - 90% non-condensing
	Certifications CE, UL, FCC Class B, ICES, VCCI



THE SECURE CHOICE™

630 Dundee Rd., Suite 210 • Northbrook, IL 60062 • Tel: 847.446.2285 • Fax: 847.441.5507 • www.digitalcheck.com

© 2022 Digital Check. ReceiptNOW, SmartSource, and The Secure Choice are trademarks of Digital Check Corp.
All other trademarks are the property of their respective owners.

Rev 03212022